Application/Control Number: 10/788,722

Art Unit: 3728

## **EXAMINER'S AMENDMENT**

An examiner's amendment to the record appears below. Should the changes and/or additions be unacceptable to applicant, an amendment may be filed as provided by 37 CFR 1.312. To ensure consideration of such an amendment, it MUST be submitted no later than the payment of the issue fee.

Authorization for this examiner's amendment was given in a telephone interview with Carrie Boone on 10/02/06. The application has been amended as follows:

Claim 1 was DELETED and REPLACED with:

- - 1. (CURRENTLY AMENDED) A tire storage system, comprising: a spacer to be placed in an opening of a tire, the opening being a cavity to dispose a rim of the tire, the rim being absent from the opening, the tire having a bead of a predetermined circumference and a hollow inside, the spacer comprising:

a top portion having a circumference greater than the predetermined circumference;

a cylindrical body having a center; and

a connecting rod disposed orthogonally through the center of the body,
two identical tire caps, a first tire cap and a second tire cap, the tire caps each
comprising a head portion and a base portion, wherein the head portion of the first tire
cap fits through the opening, and the base portion of the second tire cap is disposed
atop the tire,

the connecting rod further comprising a first tip and a second tip, wherein the first tip engages securely with the head portion of the first tire cap and the second tip

Application/Control Number: 10/788,722

Art Unit: 3728

engages securely with the head portion of the second tire cap when the first tire cap and the second tire cap are affixed to the spacer; and

the head portion further comprising a chamber having a first opening and a second opening, wherein the first tip threads through the second opening of the chamber of the first tire cap and the second tip threads through the first opening of the chamber of the second tire cap when the first tire cap and the second tire cap are affixed to the spacer;

wherein the spacer and the head portion of the first tire cap substantially fill the opening of the tire. - -

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Steven B. Pollicoff whose telephone number is (571)272-7818. The examiner can normally be reached on M-F: 7:30A.M.-4:00P.M.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Mickey Yu can be reached on (571)272-4562. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300. Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business

Application/Control Number: 10/788,722 Page 4

Art Unit: 3728

Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

ABP 10/02/06

Mickey Yu Supervisory Patent Examiner Group 3700